

CNV-SNAP-DD2 Compatibility Driver List:

Pout(W)	Driver Series	Models (×10 = mA)	Part No. Suffix	IP Rating	Input Voltage Range(Vac)
80	EBS-080S	070/105/150	BT2	IP20	176-305
100	IT 0-10 100/100-277/N E A12	0A5	A12 OP	IP20	90-305
110	SUM-110S	105/260	MF/MG/MT	IP65	90-305
150	IT 0-10 150/100-277/N E A12	0A75	A12 OP	IP20	90-305
200	IT 0-10 200/100-277/N E A12	0A9	A12 OP	IP20	90-305
220	SUM-220S	530	MF/MG/MT	IP65	90-305
220	SSM-220S	530	MF/MG/MT	IP65	249-528
240	IT 0-10 240/100-277/N E A12	1A1	A12 OP	IP20	90-305
240	EUM-240S	105/150/350/670	BG/BT/BB	IP66/IP67	90-305
320	IT 0-10 320/100-277/N E A12	1A6	A12 OP	IP20	90-305
330	SUM-330S	690	MF/MG/MT	IP65	90-305
330	SSM-330S	690	MF/MG/MT	IP65	249-528
400	NEL-400S	140	MF/MG/MT	IP65/IP66/IP67	180-457
400	NEL-400S	140	MP	IP20	180-457
400	NTL-400S	140	MP	IP20	312-528
440	SUM-440S	920	MF/MG/MT	IP65	90-305
440	SSM-440S	920	MF/MG/MT	IP65	249-528
480	EUM-480S	140/280/420/560/10A	MG/MT	IP66/IP67	90-305
480	EUM-480S	140/280/420/560/10A	BG	IP66/IP67	90-305
480	ESM-480S	140/280/420/560/10A	MG/MT	IP66/IP67	249-528
480	ESM-480S	140/280/420/560/10A	BG	IP66/IP67	249-528
500	NFM-500S	200	MG/MT	IP66/IP67	180-528
500	NFM-500S	200	GG/GT	IP66/IP67	180-528
600	NFS-600S	210	BC	IP66	180-528
680	NFM-680S	270	MG/MT	IP66/IP67	180-528
680	NFM-680S	270	GG/GT	IP66/IP67	180-528
680	NSM-680S	200	MG/MT	IP66/IP67	249-528

Pout(W)	Driver Series	Models (×10 = mA)	Part No. Suffix	IP Rating	Input Voltage Range(Vac)
680	NSM-680S	200	GG/GT	IP66/IP67	249-528
680	ESM-680S	170/240/350/560/840 /15A	BG	IP66/IP67	249-528
680	EUM-680S	170/240/350/560/840 /15A	BG	IP66/IP67	90-305
700	NSS-700S	210	BC	IP66	249-528
760	SSM-760S	15A	MG/MT	IP66/IP67	249-528
760	SSM-760S	15A	MGS	IP66/IP67	249-528
760	SUM-760S	15A	MG/MT	IP66/IP67	90-305
760	SUM-760S	15A	MGS	IP66/IP67	90-305
880	ESM-880S	280/420/700/11A/20A	MGS	IP66/IP67	249-528
880	EUM-880S	280/420/700/11A/20A	MGS	IP66/IP67	90-305
880	NFM-880S	350	MG/MT	IP66/IP67	180-528
880	NFM-880S	350	GG/GT	IP66/IP67	180-528
880	NSM-880S	270	MG/MT	IP66/IP67	249-528
880	NSM-880S	270	GG/GT	IP66/IP67	249-528
900	NFS-900S	360	BC	IP66	180-528
1000	NEL-1K0S	400	MG/MT	IP66/IP67	180-457
1000	SUM-1K0S	400/840/21A	MG/MT	IP66/IP67	90-305
1000	SUM-1K0S	400/840/20A	MGS	IP66/IP67	90-305
1000	SSM-1K0S	400/840/21A	MG/MT	IP66/IP67	249-528
1000	SSM-1K0S	400/840/20A	MGS	IP66/IP67	249-528
1200	NFM-1K2S	480	MG/MT	IP66/IP67	180-528
1200	NFM-1K2S	480	GG/GT	IP66/IP67	180-528
1200	NFS-1K2D	210	BC	IP66	180-528
1200	NSM-1K2S	350	MG/MT	IP66/IP67	249-528
1200	NSM-1K2S	350	GG/GT	IP66/IP67	249-528
1200	NSS-1K2S	360	BC	IP66	249-528
1500	NSM-1K5S	480	MG/MT	IP66/IP67	249-528
1500	NSM-1K5S	480	GG/GT	IP66/IP67	249-528

Pout(W)	Driver Series	Models (×10 = mA)	Part No. Suffix	IP Rating	Input Voltage Range(Vac)
1500	NSS-1K5D	210	BC	IP66	249-528
1500	SUM-1K5S	600/12A/31A	MG/MT	IP66/IP67	90-305
1800	NFS-1K8T	210	BC	IP66	180-528
2100	NSS-2K1T	210	BC	IP66	249-528

Notes: The table above is not an exhaustive list. Compatibility testing was performed on representative samples. If you have a question about a certain driver, please contact Inventronics.

20260112